

1	to be	to be
2	to be	to be
3	to be	to be
4	to be	to be
5	to be	to be
6	to be	to be
7	to be	to be
8	to be	to be
9	to be	to be
10	to be	to be
11	to be	to be
12	to be	to be
13	to be	to be
14	to be	to be
15	to be	to be
16	to be	to be
17	to be	to be
18	to be	to be
19	to be	to be
20	to be	to be
21	to be	to be
22	to be	to be
23	to be	to be
24	to be	to be
25	to be	to be
26	to be	to be
27	to be	to be
28	to be	to be
29	to be	to be
30	to be	to be
31	to be	to be
32	to be	to be
33	to be	to be
34	to be	to be
35	to be	to be
36	to be	to be
37	to be	to be
38	to be	to be
39	to be	to be
40	to be	to be
41	to be	to be
42	to be	to be
43	to be	to be
44	to be	to be
45	to be	to be
46	to be	to be
47	to be	to be
48	to be	to be
49	to be	to be
50	to be	to be
51	to be	to be
52	to be	to be
53	to be	to be
54	to be	to be
55	to be	to be
56	to be	to be
57	to be	to be
58	to be	to be
59	to be	to be
60	to be	to be
61	to be	to be
62	to be	to be
63	to be	to be
64	to be	to be
65	to be	to be
66	to be	to be
67	to be	to be
68	to be	to be
69	to be	to be
70	to be	to be
71	to be	to be
72	to be	to be
73	to be	to be
74	to be	to be
75	to be	to be
76	to be	to be
77	to be	to be
78	to be	to be
79	to be	to be
80	to be	to be
81	to be	to be
82	to be	to be
83	to be	to be
84	to be	to be
85	to be	to be
86	to be	to be
87	to be	to be
88	to be	to be
89	to be	to be
90	to be	to be
91	to be	to be
92	to be	to be
93	to be	to be
94	to be	to be
95	to be	to be
96	to be	to be
97	to be	to be
98	to be	to be
99	to be	to be
100	to be	to be

(M#)

**Inventor (s):** UMEDA, Atsushi  
SHIGA, Tsutomu

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
- ☒ The contents of the parent are incorporated by reference
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
- ☐ Sub. Spec Filed \_\_\_\_\_  
in App. No. \_\_\_\_\_ / \_\_\_\_\_
- ☐ Marked up Specification re  
Sub. Spec. filed \_\_\_\_\_  
In App. No. \_\_\_\_\_ / \_\_\_\_\_

## PAT-100 7/00

# LIQUID-COOLED VEHICLE ROTARY ELECTRIC MACHINE

## CROSS REFERENCE TO RELATED APPLICATION

5       The present application is based on and claims priority from Japanese Patent Application Hei 11-340558 filed November 30, 1999, the contents of which are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

10       The present invention relates to a liquid-cooled vehicle rotary electric machine driven by an internal combustion engine mounted in a vehicle, such as a passenger car or a truck.

### 15       2. Description of the Related Art

      Recently, it has been considered to use a vehicle AC generator for engine-idling-stop system or an engine-torque assisting system.

20       U.S. Patent 4,955,944 proposes a liquid-cooled rotary electric machine that has a liquid-cooled frame and a stator core fixedly fitted to the frame.

      JP-A-11-146606 proposes a liquid-cooled vehicle rotary electric machine in which coil ends of a stator winding are covered with insulation resin to be cooled by cooling liquid.

25       It is necessary to cool the stator winding by cooling liquid because the coil ends is subject to a high temperature due to its poor heat conduction.

JP-B2-2927288 proposes a vehicle AC generator in which each of a plurality of U-shaped conductor segments (hereinafter referred to as U-segment) is inserted into a pair of slots and each of the ends of the inserted U-segments is serially connected to another to form a stator winding.

As the engine idling speed has been decreasing, it has been demanded to increase electric power. On the other hand, an engine compartment has been made more compact, and a more compact vehicle AC generator has been required. The above demands have necessarily increased the maximum current or the current density of the stator winding of the generator and temperature thereof. In other words, cooling performance of the stator winding is one of decisive factors of the size of a rotary electric machine.

In a generator-motor that has a motor-function to be used for an engine-idling stop system or an engine-torque assist system, it is necessary to supply much more input current to the stator winding thereof than the output current to generate by the stator winding. As a result, the stator winding of the generator-motor presents much more serious temperature-rise problems than ordinary generators.

In order to improve cooling performance of conventional open-type air-cooled vehicle AC generator, it is possible to adopt the above liquid-cooled frame. It was found that the temperature of the stator of the rotary electric machine having the liquid-cooled frame does not become as low as the ordinary rotary electric machine, although the former has more complicated structure. This is one of major reasons why the

rotary electric machine having the liquid-cooled frame has not been put into practical use.

The other liquid-cooled vehicle rotary electric machine having multi-layered coil ends that are cooled by cooling liquid via a resinous insulator has also the following problems. It is very difficult to fill resinous material into gaps of the coil ends that are not evenly distributed. Therefore, the temperature of the conductors inside the coil ends becomes so high that the resinous material cracks due to a difference in thermal expansion between the resinous material and the conductors of the coil ends. As a result, cooling liquid (or water) may get into the inside of the coil ends through the cracks, causing short-circuiting or grounding.

There is the highest heat-transmission resistance between portions of conductor segments inside the slots and the insulators. Because the stator winding of the conventional liquid-cooled rotary electric machine is formed of round-wire coils wound one after another by a winding machine, it is very difficult to increase the conduction space factor of the slot to a certain higher value or to reduce dead spaces from the slot.

When the winding is wound by a winding machine in the manner described above, the coils overlap each other in a plurality of layers and swell in the radial direction. However, the number of conductors of the coil ends has to be limited because the spaces at opposite ends of the stator core are limited for the coil ends. This also obstructs to increase in the space factor.

Because considerably large portions of the slots are

occupied by the dead spaces, the temperature of the stator winding becomes much higher than the temperature of the insulators and the stator core although a liquid-cooled frame is provided.

5

#### SUMMARY OF THE INVENTION

The present invention has been made in view of the above problems. Therefore, a main object of the invention is to provide a compact and powerful liquid-cooled rotary electric machine.

10

A main feature of the invention is a rotary electric machine that includes a liquid-cooled frame in which liquid flows and a stator core that is fixedly fitted to the inner periphery of the frame. A stator winding is formed of a plurality of serially connected U-segments. The stator winding having the serially connected U-segments provides excellent cooling performance. As a result, a drastically smaller size-to-current ratio can be achieved.

15

There is a heat transmission channel in the rotary electric machine having a liquid-cooled frame between the heat generating stator winding and the cooling liquid. Heat is transmitted through the channel from the stator winding (including resinous insulation coating), insulators disposed between the stator winding and surfaces of slots, a stator core, a frame and the cooling liquid.

20

25

The U-segment has much larger cross-sectional area than any other round wire conductor. The U-segment also has a

rectangular cross-section that is fitted to the cross-sectional shape of the slot with very small spaces being interposed.

As the cross-sectional area is increased, the number of portions of the U-segment disposed in the slots (hereinafter referred to as the in-slot portions) can be reduced. The rectangular cross-section of the U-segment makes each in-slot portion thereof close contact with the inner wall of the slot via an insulator, thereby reducing the heat-transmission resistance.

Because of a large conduction space factor of the slot, the stator winding at the rotary electric machine according to the invention has a large cross-sectional area, which provides a low resistance of the stator winding and low temperature thereof and a high current capacity.

Because the space necessary for the coil-ends of the serially connected U-shaped conductor-segment type stator winding is small, the conduction space factor of the slot is not limited by the coil-end space, and the temperature of the stator winding can be reduced further.

For example, the conduction space factor of the slot of a conventional winding type stator is less than 50 %. This is because the cross-sectional area cannot be increased due to difficulty in the winding process.

If the cross-sectional area of the slot of the stator is the same, the heat capacity of the stator winding of the rotary electric machine according to the invention can be made much larger than the conventional rotary electric machine. This can

suppress a temperature rise even if the stator winding is supplied with a large amount of current in a short time.

Because the cross-sectional factor of the conductor segment increases, the rigidity thereof increases. The coil ends can be shaped evenly with distances between the inner periphery of the frame and the coil ends become even. Therefore, it is possible to reduce the diameter of the frame, so that the generator can be made compact.

According to another feature of the invention, the rotary electric machine is enclosed liquid-tightly. Therefore, the stator winding becomes resistant to environmental severe conditions.

According to another feature of the invention, each of the in-slot portions is closely fitted to one of the plurality of slot via an insulator. This prevents excessive temperature rise of a limited area of the in-slot portions.

According to another feature of the invention, the number of the slots is larger than the product of the number of the magnetic poles and the number of the phase of the stator.

Because the coil ends do not closely overlap one another in the radial direction, a high conduction space factor can be provided. Because the conductor segments do not overlap one another in the circumferential direction, they can closely contact the inner wall of the slots. Therefore, as the number of the slots increases, the inner surface area of the slots increases without decrease in the space factor or the contact area of the in-slot portions with the slot. Thus, an amount of

the heat dissipation can be increased, and the temperature rise of the stator winding can be suppressed more effectively.

According to another feature of the invention, each of the coil ends is separated from each other. Therefore, heat-conductive resinous material can be suitably filled in the gaps between the conductor segments of the coil ends.

Further, the insulator material does not directly contact cooling water. Therefore, there would be no chance of short-circuiting or grounding even if it cracks.

According to a further feature of the invention, the stator winding can be supplied with larger current at a motor mode than current generated at a generator mode, while suppressing the size increase and temperature rise of the stator winding.

A generator-motor for a vehicle operates as a motor to start an engine or assist an engine to accelerate the vehicle. The maximum motor current becomes a number of times as much as the maximum output current when it operates as a generator. Such maximum motor current is supplied in a comparatively a short period of time. Therefore, it is very important to suppress temperature rise of a stator winding while the vehicle generator-motor is starting or assisting the engine, in such a short period of time.

The above-stated serial U-shaped-conductor stator winding has a very high conduction space factor, very low heat resistance of the in-slot portions, and a large mass of the in-slot portions. Therefore, the stator winding can stand very large motor current in a short time.



## BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and characteristics of the present invention as well as the functions of related parts of the present invention will become clear from a study of the following detailed description, the appended claims and the drawings. In the drawings:

Fig. 1 is a longitudinal cross-sectional view of a main portion of a liquid-cooled rotary electric machine according to a first embodiment of the invention;

Fig. 2 is a radial cross-sectional view of the portion shown in Fig. 1;

Fig. 3 is a radial cross-sectional view of a portion of the stator shown in Fig. 1;

Fig. 4 is a fragmentary schematic diagram illustrating U-segments forming the stator winding shown in Fig. 1;

Fig. 5 is a fragmentary perspective view illustrating a portion of the stator shown in Fig. 1;

Fig. 6 is a fragmentary development view of the stator shown in Fig. 1 viewed from the center axis thereof in the radially outer direction;

Fig. 7 is a fragmentary development view of the stator winding shown in Fig. 1;

Fig. 8 is a fragmentary perspective view of the stator shown in Fig. 1;

Fig. 9 is a schematic diagram illustrating U-segments that form the stator winding shown in Fig. 1;

Fig. 10 is a fragmentary longitudinal cross-sectional view of a main portion of a liquid-cooled rotary electric machine according to a second embodiment of the invention;

Fig. 11 is a fragmentary longitudinal cross-sectional view of a main portion of a liquid-cooled rotary electric machine according to a third embodiment of the invention;

Fig. 12 is a fragmentary enlarged view of the stator shown in Fig. 11;

Fig. 13 is a circuit diagram of the stator winding shown in Fig. 11; and

Fig. 14 is a fragmentary longitudinal cross-sectional view of a main portion of a liquid-cooled rotary electric machine according to a fourth embodiment.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Liquid-cooled vehicle rotary electric machines according to some preferred embodiments of the invention are described with reference to the appended drawings.

A liquid-cooled rotary electric machine according to a first embodiment of the invention is described with reference to Figs. 1 and 2.

Liquid-cooled vehicle rotary machine 1 includes stator 2 that operates as an armature, rotor 3 that provides magnetic fields, and frame 4 that supports stator 2 and rotor 3.

Rotor 3 is fixedly fixed to shaft 6, a pair of pole cores 7 having a plurality of claw poles 73, connection ring 71 that connects the pair of pole cores 7, field coil 31, and stationary

yoke 72. Shaft 6 is connected with an engine crankshaft, and field coil 31 makes the pair of pole cores 7 generate magnetic field.

Ins. A' 5 ~~Field coil 31 is fitted to an annular groove that is formed in the outer periphery of stationary yoke 72 to open radially outward. Stationary yoke 72 is closely fixed to the rear end of frame 4 at the front surface thereof. The magnetic fluxes flow from field coil 3, through stationary yoke 72, radially inner portion of pole core 7, a half of all claw poles 73 of pole cores 7, stator core 32 of stator 2, the other half of claw poles 73, and stationary core 72, back to field coil 3.~~

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10

Each U-segment 33 has a pair of legs to be inserted into different slots and turn portion 33c connecting the pair of legs. Turn portion 33c projects rearward from the rear end of stator core 32. Portions of the pair of legs disposed in slots 35 are referred to as in-slot portions, and portions of the pair of the legs projecting forward from the front end of stator core 32 are referred to as projecting portions. As shown in Fig. 2, each slot 35 accommodates in-slot portion 33a at the inside layer thereof and in-slot portion 33b at the outside layer. The ends of the projecting portions are bent to extend in opposite circumferential directions to be paired with another so that each pair is welded to form joint 33d. Accordingly, turn portions 33c form rear coil ends 35 and the projecting portions form front coil ends 36.

There is a prescribed distance or space between adjacent conductor segments 33. The stator winding is formed of star-connected X, Y, and Z-phase windings. The open ends of the windings are connected to converter 5, which is connected to a battery.

The stator winding is described in more detail with reference to Figs. 3 - 9. The portions shown in Figs. 3 - 9 are denoted separately from those shown in Figs. 1 and 2.

Stator winding 1420 is a star-connected three-phase winding, which is formed of a plurality of U-segments 1433 or I-shaped conductor segments (hereinafter referred to as I-segment) whose ends are serially welded at an end of stator core 1410.

Each U-segment 1433 is formed of a flat wire coated with an insulation film, and inserted into one of two radial layers of a slot S. As shown in Fig. 4, U-segment 1433 has turn portion 1433c forming a coil end, a pair of in-slot portions 1433r, and a pair of projecting portions 1433s that respectively extend from in-slot portions 1433r. One of the pair of in-slot portions is inserted into a different slot that is  $\pi$  radian in electric angle spaced apart from the other. Each pair of projecting portions 1433s forms coil ends. The ends 1433d of projecting portions 1433s form joint portions.

The center of turn portion 1433c is located at summit 1433p of one of the projecting coil ends remote from the stator core. Turn portion 1433c extends in an axial direction and opposite circumferential directions from summit 1433p so that one side thereof extends by  $0.5\pi$  radian in electric angle in a circumferential direction. Projecting portion 1433s is also bent to extend in a circumferential direction by  $0.5\pi$  radian in electric angle.

U-segment 1433 is also bent in the radial direction at summit 1433p so that a half of U-segment 1433 including one side of turn portion 1433c, in-slot portion 1433r and projecting portion 1433s can shift in the radial direction by an approximately radial length of conductor segment 1433 from the other half including the other side of turn portion 1433c, in-slot portion 1433r and projecting portion 1433s.

Each U-segment 1433 is inserted from one end of stator core 1410 into slots S. After pairs of projecting portions 1433c of

U-segments projecting from the other end are bent in the circumferential directions, ends 1433d of the projecting portions 1433s are paired and welded to form wave-wound star-connected three-phase stator winding 1420. As shown in Fig.

5 5, one end 1433d of projecting portion 1433s projecting from the radially outer layer of one of slots S and another end 1433d of projecting portion 1433s projecting from the radially inner layer of another slot S are welded. In Fig. 4, solid lines illustrate projecting portions 1433s before bent, and two-dot-chain lines illustrate the same after bent. Turn portions 1433c are disposed on an end of stator core 1410, and projecting portions 1433s are disposed on the other end.

In Fig. 6, reference numeral 1434 indicates an insulator. Insulation sheets 1660 and 1670 are omitted from this diagram.

15 A portion of a winding diagram of the U-phase winding of three-phase-6-pole-18-slot stator winding 1420 is illustrated in Fig. 7.

The U-phase winding is formed from a series connection of wave-wound coils 1433x illustrated by a solid line and wave-wound coil 1433y illustrated by a broken line. The series connection of wave-wound coils 1433x and the series connection of wave-wound coils 1433y are shifted electric angle  $\pi$  from each other. An end of the series connection of wave-wound coil 1433x is comprised of I-segment 1436.

25 I-segment 1436, as shown in Fig. 9, is comprised of projecting portion 1436s, in-slot portion 1436r, half-turn portion 1436c, and output lead wire portion 1436z. I-segment

1436 is formed of a straight conductor segment, which is inserted into the first slots S of the wave-wound coil 1433x. Then projecting portion 1436s is bent, and end 1436d of projecting portion 1435s is welded to end 1433d of the first U-segment 1433.

5 Half-turn portion 1436c is bent to shift a half of the normal pitch of turn portion 1433c in the circumferential direction. Lead wire portion 1436z extends from one end of half turn portion 1436 over a prescribed electric angle in the circumferential direction at a prescribed distance from turn portion 1433c on the side of turn portion 1433c remote from stator core 1410. Lead wire portion 1436z further extends radially outward to connect to a connector (not shown) fixed to a wall of housing. Therefore, lead wire portion 1436z is axially disposed near turn portion 1433c of turn-side coil end group B. The other end of wave-wound coil 1433x is comprised of I-segment 1437.

I-segment 1437 has projecting portion 1437s, in-slot portion 1437r, half-turn portion 1437c, and joint portion 1437z. I-segment 1437 is formed from a straight conductor segment. The straight conductor segment is inserted into the last one of slots S of the series connection of wave-wound coils 1433x and bent at the portion corresponding to projecting portion 1433s, so that end 1437d is welded to end 1433d of U-segment 1433 of wave-wound coil 1433x.

Half-turn portion 1437c extends as long as a half of normal turn portion 1433c in the circumferential direction. Joint portion 1437z extends along a circumference around turn portions 1433c at a certain gap from turn portions 1433c over a necessary

arc length. End 1437y is welded to end 1439y of half-turn portion 1439c of I-segment 1439, which is inserted into the first one of slots S of the series connection of wave-wound coils 1433y. I-segment 1439 is the same as I-segment 1437 except joint portion 1439y. Reference numeral 1439d is the end of projecting portion 1439s of I-segment 1439, which is welded to end 1433d of the first one of U-segments 1433 of the series connection of wave-wound coils 1433y. The other end of the series connection of wave-wound coils 1433y is I-segment 1438.

I-segment 1438 has projecting portion 1438s, in-slot portion 1438r, half-turn portion 1438c, and neutral point portion 1438z. I-segment 1438 is formed of a straight conductor segment, which is inserted into the last one of slots S of the series connection of wave-wound coils 1433y. A portion corresponding to projection portion 1438s is bent, so that the end of projecting portion 1438s is welded to end 1433d of the last one of U-segments 1433. Half-turn portion 1438c extends in the circumferential direction as long as a half of normal turn portion 1433c. Neutral point portion 1438z of the U-phase winding extends in a circumference around turn portions 1433c at a distance from turn portions 1433c over a necessary arc length.

Neutral point portions 1438z of I-segments of the V-phase and W-phase windings have the same structure as neutral point portion 1438z of I-segment 1438 of the U-phase winding. However, each neutral point portion 1438z extends with others in a bundle to be welded together at its end 1438m to form the neutral point.



In this embodiment, lead wire portions 1436z, joint portions 1437z, neutral point portions 1438z are extended along the side of coil-end group B or near the axially outer side of turn-portion-side coil ends 1433c.

5        Thus the following effects of the invention can be provided.

10        All the in-slot portions can be closely fitted to the inside wall of the slots via insulators or members that are equivalent to the insulators. Therefore, all the in-slot portions can be cooled by cooling water evenly and sufficiently via stator core 32 and front frame 42.

15        ~~The number of slots is more than three (corresponding to the number of phases) times as many as the number of the magnetic poles. For example, not 96 slots (that is three times as many as 32 poles) but 192 slots are provided for a 32-pole-three-phase generator; or 144 slots are provided for a 24-pole-three-phase generator. The extra-many-slot structure increases the contact area of the in-slot portions of conductor segments 33 with the slot inner walls via insulators, so that the heat dissipation~~  
20 ~~of conductor segments can be more improved.~~

The temperature of coil ends 35 and 36 becomes higher than other portions, contrary to the open type rotary electric machine.

25        The radial thickness and the axial length of the coil ends of the stator winding formed of serially connected U-segments can be reduced much from a corresponding continuously-wound-wire type stator winding. The volume and average length (from the

in-slot portions) of the coil ends can be reduced so that the temperature rise of the coil ends of conductor segments 33 can be drastically reduced.

Heat of the coil ends 35 and 36 can be conducted to the in-slot portion much, thereby to suppress the temperature rise of the coil ends effectively.

Because a sealed type rotary electric machine can be provided without minding temperature rise of the stator winding, a much stronger rotary electric machine against the environmental conditions than conventional rotary electric machine can be provided.

The distance between frame 4 and coil ends 35, 36 is arranged to be more than 2 mm to reduce eddy current loss of frame 4 caused by alternating magnetic fields. It is possible that coil ends 35 and 36 are bent radially inward to increase the above distance. Because conductor segments 33 are rigid enough to keep the distance unchanged, the shape of coil of coil ends 35 and 36 can be maintained unchanged. This can omit the insulation film coating of conductor segments 33.

The conduction space factor can be increased more than 70 %.

Since two or four U-segments are radially aligned and inserted into each slot, all the in-slot portions are fitted to the inner walls of the slots via insulators. In addition, at least other two or more surfaces of the U-segment can be fitted to the inner walls of the slots of the heat dissipating stator core via insulators.

None of the in-slot portions is excessively heated to increase the temperature thereof higher than the heat resistant temperature of the insulation coating of the stator winding.

If the generator-motor is supplied to start an engine with much larger amount of input current than output current generated by the same, temperature rise of the stator winding in a short time can be suppressed. Because, the volume of the stator winding relative to the stator core and the heat capacity thereof can be increased.

The liquid-cooled rotary electric machine can be connected to the crankshaft via a belt or a chain as the conventional alternators. This rotary electric machine can be directly connected to the crankshaft or via a gear unit.

This liquid-cooled vehicle rotary electric machine can be used for a generator or a motor. The structure of the rotor or the stator winding can be changed to different types of structure.

A liquid-cooled vehicle rotary electric machine according to a second embodiment of the invention is described with reference to Fig. 10.

This embodiment is characterized in that front coil ends of the liquid-cooled vehicle rotary electric machine according to the first embodiment is molded with a heat-conductive resin 300 and brought in contact with the inner periphery and the inside end of front frame 42 of the same embodiment.

In other words, each conductor segment 33 forming coil ends

36 is separated from others other at even gaps. Therefore, it is easy to fill fluid resin 300 into the gaps for the molding.

In addition, the heat of coil ends 36 can be conducted through resin 300 to frame 4, so that the temperature of coil ends 36 can be lowered. Because resin 300 is not in direct contact with the cooling liquid, grounding or short-circuiting of the stator winding would not occur even if resin 300 cracks.

It is also possible to mold coil ends 35 with the same resin.

A liquid-cooled rotary electric machine according to a third embodiment of the invention is shown in Figs. 11 - 13.

This embodiment is the same as the first embodiment except the following: the number of the conductor segments 33 in a slot is 4; there are two three-wave stator windings 1001 and 1002; and two converter 1003 and 1004 are provided. Because there are two circuit systems, the rotary electric machine becomes more reliable.

A liquid-cooled rotary electric machine according to a fourth embodiment of the invention is shown in Fig. 14.

This embodiment is the same as the first embodiment except the following: two openings connected to cooling water passage 41 are formed at the inner periphery of frame 4 so that cooling water can directly contact the outer periphery of stator core 32. O-ring 500 is disposed around two openings 410. Therefore, the cooling performance of the stator winding can be improved more.

A liquid-cooled rotary electric machine according to a fifth embodiment of the invention is described hereafter.

This embodiment is the same as the first embodiment except insulator 34, which is modified.

Insulator 34 of this embodiment is made from fine powder of heat-conductive nonmagnetic insulation-resin such as polyimide-contained resin.

Thus, heat transmission resistance, which has been a fatal obstacle to practical use of the rotary electric machine having a liquid-cooled frame, can be drastically reduced without reducing effective magnetic flux or increasing iron loss or copper loss. This can reduce the temperature of the stator winding further.

In the foregoing description of the present invention, the invention has been disclosed with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made to the specific embodiments of the present invention without departing from the broader spirit and scope of the invention as set forth in the appended claims. Accordingly, the description of the present invention is to be regarded in an illustrative, rather than a restrictive, sense.